



UV-1500

Ultra Violet Water Sterilizer

Description



The UV-1500 is a robust, high quality ultra-violet water sterilizer that offers very efficient treatment at a low cost per unit volume. Typically installed at the point of entry, it can treat municipal water as well as ground water from drilled or dug wells, or surface water from lakes, ponds or rivers (pre-filtration necessary). This sterilizer is perfectly sized to provide drinking water or purified process water for large houses and mansions, as well as for commercial and light industrial applications.

The model UV-1500 sterilizer contains a low-pressure, high output UV lamp in a 316L stainless steel reaction chamber. The electronic ballast remembers when it is time to install a new UV replacement lamp with an automatic countdown display and alarm.

Combined with appropriate pre-filtration, this UV sterilizer is the centre piece of a complete water treatment system for the elimination of bacteria and viruses and reduction of taste and odour at the point of entry (see SYS1500/QS4E-1/2).

Additional features are available, such as a UV-monitoring system for fail-safe operation, a thermo-sensitive purge valve at the out port to prevent overheating under no-flow conditions, and volt-free contacts for remote signaling.

The UV-1500 kills most harmful microbiological contaminants, such as viruses, bacteria and protozoa with a powerful UV disinfection dose that will inactivate the pathogens at a kill rate of 99.99% (log 4) or more (*Giardia*, *E. coli*, *Cryptosporidium*, *Vibrio cholerae*, *Legionella*, *Salmonella*, *Shigella*, *Streptococcus* and many others).



Applications

- ▶ Potable Water, Process Water
- ▶ Commercial and Light Industrial Applications
- ▶ Pharmaceutical Manufacturing
- ▶ Butcher Shops
- ▶ Hotels and Restaurants
- ▶ Pools and Spa's
- ▶ Food and Beverage Processing

Benefits

- ▶ Efficient Disinfection, Low Cost per Litre
- ▶ Exceptional High UV Dose
- ▶ Extremely Simple to Use and Maintain
- ▶ High Quality Stainless Steel Reaction Chamber
- ▶ Easily Upgradeable with Optional Features
- ▶ Made in Canada




Specifications

Part # P1500/QS4E-1/2

Flow Range:	68 - 168 litres per minute (17.9 - 44.3 GPM) 4,020 l (4.02m ³) - 10,080 l (10.08 m ³) /hour / 96.5 - 241.9 m ³ /day 1,074 - 2,658 gallons/hour, 25,776 - 63,792 gallons/day
UV Dose Applied (95% UVT):	16 mJ/cm ² (16,000 μWsec/cm ²) @ 168 LPM / 44.3 GPM 30 mJ/cm ² (30,000 μWsec/cm ²) @ 92 LPM / 24.7 GPM 40 mJ/cm ² (40,000 μWsec/cm ²) @ 68 LPM / 17.9 GPM
Electrical:	110 Volt AC / 50 - 60 Hz (Part # P1500/QS4E-1) 240 Volt AC / 50 - 60 Hz (Part # P1500/QS4E-2)
Ballast:	Electronic Ballast w/ Lamp Out Alarm, Power LED, Running Days Countdown on LCD Display (Resettable) Model RH51-800-95L (Wyckomar Part # 4-BE-800-ECO)
Ballast Enclosure Rating:	IP64
Lamp Current:	0.75 A - 0.85 A / U-Out: 300 V / PF(λ): > 0.99% / THD: < 10%
Number of Lamps:	1 at 110 Watts, 800 mA (Part # RL-110/1197T5) Low-Pressure UV
UV Monitor:	Optional (Part # 4-UV/MS-1/2 V3)
Min/Max. Operating Temperature:	T _{min.} = 3 °C (37 °F), T _{max.} = 40 °C (104 °F)
Max. Operating Pressure:	125 psi - 8.6 bar
Plumbing:	1" MNPT In/Out
Chamber Material:	316L Stainless Steel
Shipping Size and Weight:	1 box 52x9x9 inches, 17 lbs / 7.8 kg

Specifications subject to change

Dose Chart



Additional Features (Optional):

- Electronic Deposit Control System with PVC or Stainless Reaction Chamber
- Volt-Free Contacts on Ballast for Remote Signaling
- Purge Valve at Out Port for Overheat Protection
- Rack- or Panel-Mounted for Easy Installation

Important Considerations

This UV sterilizer assumes certain water quality parameters to be met for proper operation. If the source water does not meet the following criteria, pretreatment has to be considered:

Turbidity (Suspended Solids): Must be < 1 NTU at the time of disinfection. There must be a 5 micron or less sediment prefiltration system installed before the UV system.

Total Hardness (Sum of Calcium and Magnesium): Must be < 10 gpg (grains per gallon)

Iron: Must be < 0.3 ppm (parts per million)

Manganese: Must be < 0.05 ppm

This UV unit is available as complete system with appropriate pre-filtration (Part # SYS1500/QS4E-1/2) and can be customized for many applications with pre-filtration into an All-in-One rack mounted system.